

Datasheet

Version 01 (TK) 01-07-2020

Product Name ALKYLATE GASOLINE 2S RELIANT

Material no.: 29491, 29492, 29493

TYPICAL SPECIFICATION

1. Alkylate Gasoline

Parameter	Unit	Specification	Typical value
Research Octane Number, RONc	-	min 93	94.2
Motor Octane Number, MONc	-	min 90	91.6
Density (15°C)	kg/m ³	680 - 720	686
Lead	mg/l	max 2	< 1
Sulphur	mg/kg	max 10	< 1
Aromatics	vol-%	max 0.5	0.35
Olefins	vol-%	max 0.5	0.1
Benzene	vol-%	max 0.09	0.01
Existent Gum, washed	mg/100ml	max 3	< 1
Vapour pressure, DVPE	kPa	55 - 65	58
Distillation 70°C (E70)	vol-%	15 - 42	27
Distillation 100°C (E100)	vol-%	46 - 72	47
Final Boiling point	°C	max 200	181
Distillation residue	vol-%	max 1	1
Total Fluorine content	mg/kg	-	< 20
2-Stroke oil content*	vol-%	1.9 - 2.2	2

All Analysis made by our supplier.

*2-Stroke oil content analysis made by Brenntag Nordic

Brenntag Nordic, Koksgatan 18, Box 50 121, 202 11 Malmö, Sweden - Tel +46 40 28 73 00

The above information is provided for our customers and (we accept no liability to any third parties) reflects our current knowledge and experience of the product. All products are supplied in accordance with the relevant conditions of sale of Brenntag Nordic. Brenntag Nordic can accept no liability for the effects of any chemical combinations or mixtures of the products which are carried out by our customers or third parties. In using the product our customers are reminded to comply with all relevant legal, administrative and regulatory requirements and procedures relating to its use and the protection of the environment.

TYPICAL SPECIFICATION**2. 2-Stroke oil**

Parameter	Unit	Typical Value	
Appearance	-	Green	
Density, 20°C	kg/dm ³	0.932	
Flash point, coc	°C	258	
Pour point	°C	- 39	
Total acid number	mg KOH/g	0.12	
TBN	mg KOH/g	3.83	
Kinematic viscosity	100°C	mm ² /s	8.2
	40°C	mm ² /s	47
Dynamic viscosity	- 25°C	mPa.s	4170
Sulphated ash – mass fraction	%	0.01	
Biodegradability	%	61.9	

This table shows typical values, no analysis made.

STORAGE and SAFETY

For storage and safety information please see safety datasheet.

Approved by: Jonas Larsson, Product Manager

Brenntag Nordic, Koksgatan 18, Box 50 121, 202 11 Malmö, Sweden - Tel +46 40 28 73 00

The above information is provided for our customers and (we accept no liability to any third parties) reflects our current knowledge and experience of the product. All products are supplied in accordance with the relevant conditions of sale of Brenntag Nordic. Brenntag Nordic can accept no liability for the effects of any chemical combinations or mixtures of the products which are carried out by our customers or third parties. In using the product our customers are reminded to comply with all relevant legal, administrative and regulatory requirements and procedures relating to its use and the protection of the environment.